

# High pressure fully electronic steam generators

MOD. SG 15

MOD. SG 39

MOD. SG 48



Available in 3 models, SG 15, SG 39 & SG 48.

Photo: mod. SG 39 with E / T 7539

For steam supply to 4-20 irons (or to steam presses). All boiler functions are electronically controlled through a brain-card. Malfunctions warning. Touch buttons keyboard. Main switch for the power ON/OFF. Water level gauge. Possibility for a TIMER connection for the start timing. Water feeding by an INOX tank of 75lt capacity. Series SG steam boilers meets safety standards and official regulations being tested by TÜV & carrying a TRD801-TRD802 certificate and a CE conformity certification. The machine body is volume limited for place saving.

## TECHNICAL DATA

	mod. SG 15	mod. SG 39	mod. SG 48
Heating power	: 18 KW	19,5 - 39 KW	24+24KW
Steam pressure	: 5 bar	6 bar	6 bar
Steam consumption	: 19,5 Kg/h	2 programs 26-52 Kg/h	2 programs 32-64 Kg/h
Power supply	: 400 V-3 ph.-50 Hz	400 V-3 ph.-50 Hz	400 V-3 ph.-50 Hz
Water feeding	: by tank INOX 75lt.Mod. E/T7515	by tank INOX 75lt. Mod. E/T7539	by tank INOX 75lt. Mod. E/T7539
Overall dimensions	: L 420 W 580 H 760mm	L 530 W 705 H 880mm	L 530 W 705 H 880mm

\* To the mod. SG15 the water pump 0.7HP is built in the machine.

\* To the mod. SG39 the water pump 0.7HP is built in the tank E/T7539.

\* To the mod. SG48 the water pump 0.9HP is built in the tank E/T7539.