

# Steamy

## High pressure steam generator 10bar for continuous operation

Available in 3 models. All functions are electronically controlled through an electronic plate. Suitable for fur, dentistry, jewellery etc. workshops.

### Special Features:

- Electronic level control system through 1 electrode.
- Cylinder steel Boiler 8 L / thickness 4.5mm  
(The water drops glide down to the bottom of the boiler)
- Outside and inside welding of the boiler to avoid oxidation
- Double steam outlet for 2 Irons which keeps the steam dry
- Water inlet through a copper tube Ø12mm
- External Safety valve, according to the TUV safety regulations
- External water tank 20L
- Wheels for easy transport and service

Steel Boiler.....8 L

Operating pressure.....10 bar

Test pressure.....17 bar



Steam Gun PSH/V

### Steam guns come as extra accessories

**PSH/V** Steam-heating gun with steam trap for return condensates. There is steam chamber to produce dry steam without water and bakelite handle with a button.

**PA** Small steam spraying gun with accessory set and 4-pole plug.

Model	Code	Features	Volt	Heating kW	Steam Kg/h
<b>STEAMY 2-6</b>	103-07-002	With 2 steam valve. Steam supply for 1 steam gun & steam iron	230	6	7.8
<b>STEAMY 2-6</b>	103-06-003	With 1 steam valve. Steam supply for 1 steam gun & steam iron	400	6	7.8
<b>STEAMY 2-9</b>	103-06-001	With 2 steam valve. Steam supply 1 steam gun & steam iron	400	10.5	13.6

Packaging	Dimensions	Net Weight Kg	Gross Weight Kg
<b>Cardboard</b>	65 x 46 x 102 cm	<b>45</b>	<b>51</b>
<b>Pallet</b>			

### Accessories:

Model	Code	Description
<b>PSH/V</b>	106-13-003	Steam-heating gun with steam trap for return condensates
<b>PA</b>	106-13-000	Steam Gun With Set of Tools and 4pole plug
<b>FLOATING SYSTEM KIT</b>	303-03-041-1	Float tank with floating system for direct connection to the water line. Can be supplied after request with extra cost.
<b>ANTISCAL 1Kg</b>	200-06-146	Water soluble polymer that prevents deposits of lime



PSH/V



PA



Floating System Kit



Antiscal