

# Vapormat

**Industrial electric steam generator for continuous operation** Available in 6 models depending on the power from 2.5KW up to 6KW. Different connections for one, two or three steam irons.

**Equipped with fault detection program and electronic keyboard with touch buttons.** All functions are electronically controlled by a PCB. Suitable for garment industry, dry cleaning shop, tailors shops and ateliers.

**Special Features:**

- Electronic level control system by 3 electrodes.
- Fault detection program and electronic keyboard with touch buttons.
- Cylinder steel Boiler 8.5 L / thickness 6.5mm.  
(The water drops glide down to the bottom of the boiler)
- Outside and inside welding of the boiler to avoid oxidation
- Double steam outlet for 2 Irons which keeps the steam dry
- Water inlet through a copper tube Ø12mm
- External Safety valve, according to the TUV safety regulations
- External water tank 20L.
- Wheels for easy drive and service

Steel Boiler.....Steel 8.5 L  
 Operating pressure.....3.5 bar or **(4.5 bar after request)**  
 Test pressure.....6 bar

For the trouble free operation of the steam generator we recommend the use of our binding agent **Antiscal**.



**Boiler 8.5L**

Model	Code	Features	Volt	Heating kW	Steam Kg/h
VAPORMAT 1-2.5	103-03-000	With 1 steam valve. Steam supply for 1 steam iron	230	2.5	3.25
VAPORMAT 1-4	103-03-001	With 1 steam valve. Steam supply for 1 steam iron	230	4	5.2
VAPORMAT 2-4	103-03-003	With 2 steam valve. Steam supply for 2 steam iron	230	4	5.2
VAPORMAT 2-4	103-03-004	With 2 steam valve. Steam supply for 2 steam iron	400	4	5.2
VAPORMAT 2-6	103-03-005	With 2 steam valve. Steam supply for 2 steam iron	400	6	7.8
VAPORMAT 3-6	103-03-006	Steam supply for 3 irons	400	6	7.8
<b>All models can be supplied with 4.5 Bar pressure after request with extra cost</b>					

Packaging	Dimensions	Net Weight Kg	Gross Weight Kg
Cardboard	65 x 50 x 102 cm	48	52

**Accessories:**

Model	Code	Description
FLOATING SYSTEM KIT	303-03-041-1	Floating System Kit for water tank to be connected to direct water connection. Can be supplied after request with extra cost.
BLOW-OFF TANK 10L	303-03-039	Water tank for vaporization
ANTISCAL 1Kg	200-06-135	Water soluble polymer that prevents deposits of lime



**Floating System Kit**



**Blow-off Tank 10L**



**Antiscal**